According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## HARDENER HV 998-1

Version Revision Date: SDS Number: Date of last issue: 16.07.2022 1.5 04.11.2023 40000000524 Date of first issue: 19.05.2016

Print Date 22.04.2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : HARDENER HV 998-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Hardener

Substance/Mixture

Recommended restrictions : For industrial use only.

on use

1.3 Details of the supplier of the safety data sheet

Company : HUNTSMAN ADVANCED MATERIALS (UK) LIMITED

Address : Ickleton Road, Duxford, Cambridgeshire

CB22 4XQ United Kingdom

Telephone : +41 61 299 20 41

E-mail address of person

responsible for the SDS

: Global\_Product\_EHS\_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : EUROPE: +32 35 75 1234

France ORFILA: +33(0)145425959

ASIA: +65 6336-6011 China: +86 20 39377888 +86 532 83889090 India: + 91 22 42 87 5333

Australia: 1800 786 152 New Zealand: 0800 767 437 USA: +1 800-424-9300

#### **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard,

Category 2

H411: Toxic to aquatic life with long lasting effects.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## HARDENER HV 998-1

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 16.07.2022

 1.5
 04.11.2023
 400000000524
 Date of first issue: 19.05.2016

Print Date 22.04.2024

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :







Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P261 Avoid breathing mist or vapours.P264 Wash skin thoroughly after handling.P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTER/ doctor. P391 Collect spillage.

Hazardous components which must be listed on the label:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine Amines, polyethylenepoly-, triethylenetetramine fraction

# 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### **SECTION 3: Composition/information on ingredients**

# 3.2 Mixtures

Chemical nature : Amines

#### **Hazardous components**

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concent ration (% w/w)
Reaction products of fatty acid	Not Assigned	Skin Irrit. 2; H315	>= 30 -

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## HARDENER HV 998-1

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 16.07.2022

 1.5
 04.11.2023
 400000000524
 Date of first issue: 19.05.2016

Print Date 22.04.2024

dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction	-	Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	< 50	
N'-(3-aminopropyl)-N,N- dimethylpropane-1,3-diamine	10563-29-8 234-148-4	Acute Tox. 4; H302 Skin Corr. 1A; H314 Eye Dam. 1; H318 Skin Sens. 1B; H317 specific concentration limit Skin Corr. 1A; H314 >= 29.85 % Skin Corr. 1B; H314 9.65 - < 29.85 % Skin Corr. 1C; H314 5 - < 9.65 %	>= 3 - < 5	
Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8 292-588-2	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 3 - < 5	
Substances with a workplace exposure limit :				
barium sulfate	7727-43-7		>= 50 -	
For explanation of abbreviations	231-784-4		< 70	

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Treat symptomatically.

Get medical attention if symptoms occur.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

If potential for exposure exists refer to Section 8 for specific

personal protective equipment.

Avoid inhalation, ingestion and contact with skin and eyes. No action shall be taken involving any personal risk or without

suitable training.

It may be dangerous to the person providing aid to give

mouth-to-mouth resuscitation.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## HARDENER HV 998-1

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 16.07.2022

 1.5
 04.11.2023
 400000000524
 Date of first issue: 19.05.2016

Print Date 22.04.2024

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

Exercise caution when using a high volume water jet as it may

scatter and spread fire

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Ammonia Carbon oxides

Nitrogen oxides (NOx)

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## HARDENER HV 998-1

Version Revision Date: SDS Number: Date of last issue: 16.07.2022 1.5 04.11.2023 40000000524 Date of first issue: 19.05.2016

Print Date 22.04.2024

Specific extinguishing

methods

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

#### **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Refer to protective measures listed in sections 7 and 8.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Neutralise with acid.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

#### **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

Advice on safe handling : Repeated or prolonged skin contact may cause skin irritation

and/or dermatitis and sensitisation of susceptible persons. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this

product.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against : Normal measures for preventive fire protection.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## HARDENER HV 998-1

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 16.07.2022

 1.5
 04.11.2023
 400000000524
 Date of first issue: 19.05.2016

Print Date 22.04.2024

fire and explosion

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

# 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully

resealed and kept upright to prevent leakage. Keep in properly

labelled containers.

Advice on common storage : Do not store near acids.

Further information on

storage stability

Stable under normal conditions.

Recommended storage

temperature

: 2 - 40 °C

7.3 Specific end use(s)

Specific use(s) : No data available

## **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

# **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parameters	Basis
		of exposure)		
barium sulfate	7727-43-7	TWA (inhalable	10 mg/m3	GB EH40
		dust)		
		TWA (Respirable	4 mg/m3	GB EH40
		dust)	_	

# **Derived No Effect Level (DNEL):**

Substance name	End Use	Exposure routes	Potential health effects	Value
barium sulfate	Workers	Inhalation	Long-term systemic effects	10 mg/m3
	Workers	Inhalation	Long-term local effects	10 mg/m3
	Consumer use	Inhalation	Long-term systemic effects	10 mg/m3
	Consumer use	Oral	Long-term systemic effects	13000 mg/kg
N'-(3-aminopropyl)- N,N-dimethylpropane- 1,3-diamine	Workers	Inhalation	Long-term systemic effects	3.7 mg/m3
	Workers	Inhalation	Acute systemic effects	7.5 mg/m3

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# **HARDENER HV 998-1**

Version Revision Date: SDS Number: Date of last issue: 16.07.2022 1.5 04.11.2023 40000000524 Date of first issue: 19.05.2016

Print Date 22.04.2024

	Workers	Inhalation	Long-term local effects	3.7 mg/m3
	Workers	Inhalation	Acute local effects	7.5 mg/m3
	Workers	Dermal	Long-term systemic effects	0.67 mg/kg
	Consumers	Inhalation	Long-term systemic effects	0.65 mg/m3
	Consumers	Inhalation	Long-term local effects	0.65 mg/m3
	Consumers	Oral	Long-term systemic effects	0.2 mg/kg
Amines, polyethylenepoly-, triethylenetetramine fraction	Workers	Inhalation	Long-term systemic effects	0.54 mg/m3
	Consumers	Inhalation	Long-term systemic effects	0.096 mg/m3
	Consumers	Oral	Long-term systemic effects	14 mg/kg bw/day

#### **Predicted No Effect Concentration (PNEC):**

Substance name	Environmental Compartment	Value		
barium sulfate	Fresh water	115 μg/l		
	Sewage treatment plant	62.2 mg/l		
	Remarks: Assessment Factors			
	Fresh water sediment	600.4 mg/kg		
	Remarks: Assessment Factors			
	Soil	207.7 mg/kg		
	Remarks: Assessment Factors			
N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine	Fresh water	9.2 μg/l		
	Remarks:Assessment Factors			
	Marine water	0.92 μg/l		
	Remarks: Assessment Factors			
	Freshwater - intermittent	92 µg/l		
	Remarks: Assessment Factors			
	Sewage treatment plant	18.1 mg/l		
	Remarks: Assessment Factors	<u> </u>		
	Fresh water sediment	0.0336 mg/kg dry weight (d.w.)		
	Marine sediment	0.0034 mg/kg dry weight (d.w.)		
	Soil	0.0013 mg/kg dry weight (d.w.)		
Amines, polyethylenepoly-, triethylenetetramine fraction	Fresh water	0.027 mg/l		
	Marine water	0.003 mg/l		
	Sewage treatment plant	0.13 mg/l		
	Fresh water sediment	8.572 mg/kg dry weight (d.w.)		
	Marine sediment	0.857 mg/kg dry weight (d.w.)		
	Soil	1.25 mg/kg dry weight (d.w.)		

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# **HARDENER HV 998-1**

Version Revision Date: SDS Number: Date of last issue: 16.07.2022 1.5 04.11.2023 40000000524 Date of first issue: 19.05.2016

Print Date 22.04.2024

#### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Material : butyl-rubber

Break through time : > 8 h

Material : Nitrile rubber Break through time : 10 - 480 min

Material : Ethyl Vinyl Alcohol Laminate (EVAL)

Break through time : > 8 h

Remarks : The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain,

duration of contact).

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : WARNING! This product contains quartz, which has

been classified by IARC as carcinogenic for humans (Group 1), and which can cause silicosis and lung cancer following exposure to respirable dust. It is therefore important to take

particular care to avoid inhalation exposure when mechanically processing cured material (e.g. grinding,

sanding, sawing).

# **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state : paste

Colour : grey

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# **HARDENER HV 998-1**

Version Revision Date: SDS Number: Date of last issue: 16.07.2022 1.5 04.11.2023 40000000524 Date of first issue: 19.05.2016

Print Date 22.04.2024

Odour : amine-like

Odour Threshold : No data is available on the product itself.

Melting point/freezing point : No data is available on the product itself.

Boiling point : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Lower explosion limit / Lower

flammability limit

: No data is available on the product itself.

Upper explosion limit / Upper

flammability limit

: No data is available on the product itself.

Flash point : > 100 °C

Method: Pensky-Martens closed cup

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : No data is available on the product itself.

pH : ca. 12 (20 °C)

Concentration: 500 g/l

Viscosity

Viscosity, dynamic : 60,000 - 80,000 mPa,s (20 °C)

Solubility(ies)

Water solubility : practically insoluble (20 °C)

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-

octanol/water

: No data is available on the product itself.

Vapour pressure : < 0.95 hPa (25 °C)

Density : 1.6 g/cm3 (25 °C)

Relative density : No data is available on the product itself.

Relative vapour density : No data is available on the product itself.

Particle characteristics : No data is available on the product itself.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## HARDENER HV 998-1

Version Revision Date: SDS Number: Date of last issue: 16.07.2022 1.5 04.11.2023 40000000524 Date of first issue: 19.05.2016

Print Date 22.04.2024

#### 9.2 Other information

No data is available on the product itself.

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

Stable under normal conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

#### 10.4 Conditions to avoid

Conditions to avoid : None known.

# 10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases

Strong oxidizing agents

None known.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

Hazardous decomposition : ammonia, anhydrous

products Aldehydes

Nitrogen oxides (NOx) carbon monoxide carbon dioxide

Ketones

#### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

# **Acute toxicity**

Not classified due to lack of data.

#### **Product:**

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

#### **Components:**

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18

(unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## HARDENER HV 998-1

Version Revision Date: SDS Number: Date of last issue: 16.07.2022 1.5 04.11.2023 40000000524 Date of first issue: 19.05.2016

Print Date 22.04.2024

Method: OECD Test Guideline 423

Assessment: The substance or mixture has no acute oral

toxicity

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

# N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Acute oral toxicity : LD50 (Rat, male and female): 1,669 mg/kg

Method: OECD Test Guideline 401

GLP: no

Assessment: The component/mixture is moderately toxic after

single ingestion.

## Amines, polyethylenepoly-, triethylenetetramine fraction:

Acute oral toxicity : LD50 (Rat, male and female): 1,716.2 mg/kg

Method: OECD Test Guideline 401

Assessment: The component/mixture is moderately toxic after

single ingestion.

Acute dermal toxicity : LD50 (Rabbit, male and female): 1,465.4 mg/kg

Method: OECD Test Guideline 402

Assessment: The component/mixture is moderately toxic after

single contact with skin.

barium sulfate:

Acute oral toxicity : LD50 (Rat, male): 307 - 364 g/kg

Method: OECD Test Guideline 401

# Skin corrosion/irritation

Causes skin irritation.

**Product:** 

Result : Skin irritation

#### **Components:**

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Species : human skin

Assessment : May cause eye and skin irritation.

Method : OECD Test Guideline 431

Result : May cause eye and skin irritation.

Species : human skin Assessment : Irritant

Method : OECD Test Guideline 439

Result : Irritating to skin.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## HARDENER HV 998-1

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 16.07.2022

 1.5
 04.11.2023
 400000000524
 Date of first issue: 19.05.2016

Print Date 22.04.2024

#### N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Species : Rabbit

Assessment : Causes severe burns.

Method : OECD Test Guideline 404

Result : Extremely corrosive and destructive to tissue.

GLP : ves

## Amines, polyethylenepoly-, triethylenetetramine fraction:

Species : reconstructed human epidermis (RhE)

Assessment : Causes burns.

Method : OECD Test Guideline 435

Result : Corrosive after 3 minutes to 1 hour of exposure

Species : Rabbit

Assessment : Causes burns.

Method : OECD Test Guideline 404

Result : Corrosive after 3 minutes to 1 hour of exposure

#### barium sulfate:

Species : human skin
Assessment : No skin irritation
Result : No skin irritation

#### Serious eye damage/eye irritation

Causes serious eye damage.

#### **Components:**

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Species : Rabbit

Method : OECD Test Guideline 405

Result : Corrosive

#### N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Assessment : Risk of serious damage to eyes. Result : Risk of serious damage to eyes.

GLP : no

# Amines, polyethylenepoly-, triethylenetetramine fraction:

Species : Rabbit

Assessment : Risk of serious damage to eyes.

Method : OECD Test Guideline 405

Result : Irreversible effects on the eye

#### barium sulfate:

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

## HARDENER HV 998-1

Version Revision Date: SDS Number: Date of last issue: 16.07.2022 1.5 04.11.2023 40000000524 Date of first issue: 19.05.2016

Print Date 22.04.2024

#### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

#### Respiratory sensitisation

Not classified due to lack of data.

#### Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Exposure routes : Skin Species : Mouse

Method : OECD Test Guideline 429

Result : The product is a skin sensitiser, sub-category 1A.

# N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Test Type : Maximisation Test

Exposure routes : Skin Species : Guinea pig

Assessment : Probability or evidence of low to moderate skin sensitisation

rate in humans

Method : OECD Test Guideline 406

Result : Probability or evidence of low to moderate skin sensitisation

rate in humans

GLP : yes

#### Amines, polyethylenepoly-, triethylenetetramine fraction:

Exposure routes : Skin

Species : Guinea pig

Assessment : Probability or evidence of skin sensitisation in humans

Method : OECD Test Guideline 406

Result : Probability or evidence of skin sensitisation in humans

barium sulfate:

Exposure routes : Skin Species : Mouse

Method : OECD Test Guideline 429

Result : Does not cause skin sensitisation.

#### Germ cell mutagenicity

Not classified due to lack of data.

#### Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Metabolic activation: with and without metabolic activation

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## HARDENER HV 998-1

Version Revision Date: SDS Number: Date of last issue: 16.07.2022 1.5 04.11.2023 40000000524 Date of first issue: 19.05.2016

Print Date 22.04.2024

Method: OECD Test Guideline 476

Result: negative

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 487

Result: negative

# N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Test system: Human lymphocytes

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 487

Result: negative GLP: yes

Test Type: reverse mutation assay Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

GLP: yes

Test Type: reverse mutation assay

Test system: Salmonella tryphimurium and E. coli

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

#### Amines, polyethylenepoly-, triethylenetetramine fraction:

Genotoxicity in vitro : Test Type: reverse mutation assay

Test system: Salmonella tryphimurium and E. coli

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive GLP: yes

Test Type: Micronucleus test Test system: Human lymphocytes

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 487

Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse (male and female)

Cell type: Bone marrow

Application Route: Intraperitoneal injection

Dose: 0 - 600 mg/kg

Method: OECD Test Guideline 474

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

## HARDENER HV 998-1

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 16.07.2022

 1.5
 04.11.2023
 400000000524
 Date of first issue: 19.05.2016

Print Date 22.04.2024

Result: negative

barium sulfate:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

### Carcinogenicity

Not classified due to lack of data.

## **Components:**

#### N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Species : Mouse, male
Application Route : Dermal
Exposure time : 20 month(s)

Dose : 1.25/56.3 mg/animal

Frequency of Treatment : 3 daily

NOAEL : >= 56.3 mg/kg body weight

Result : negative

Remarks : Information given is based on data obtained from similar

substances.

# Amines, polyethylenepoly-, triethylenetetramine fraction:

Species : Mouse, male Application Route : Dermal

NOAEL : >= 50 mg/kg bw/day
Method : OECD Test Guideline 451

Result : negative

Species : Mouse, male Application Route : Dermal Exposure time : 104 weeks

NOAEL : >= 20 mg/kg bw/day
Method : OECD Test Guideline 451

Result : negative

barium sulfate:

Species : Rat, male and female

Application Route : Oral
Exposure time : 104 weeks
Dose : 60 - 75 mg/kg
Method : OPPTS 870.4200

Result : negative

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAI

Enriching lives through innovation

# HARDENER HV 998-1

Version Revision Date: SDS Number: Date of last issue: 16.07.2022 40000000524 1.5 04.11.2023 Date of first issue: 19.05.2016

Print Date 22.04.2024

Species Mouse, male and female

**Application Route** Oral

Dose 160 - 200 mg/kg Method OPPTS 870.4200

Result negative

# Reproductive toxicity

Not classified due to lack of data.

#### Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Effects on fertility Species: Rat, male and female

Application Route: Oral

Method: OECD Test Guideline 422

Result: Animal testing did not show any effects on fertility.

#### N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Effects on fertility Test Type: OECD Test Guideline 422

Species: Rat, male and female

Application Route: Oral

Dose: 5. 15 and 50 mg/kg bw/d

General Toxicity - Parent: NOAEL: 15 mg/kg body weight General Toxicity F1: NOAEL: 15 mg/kg body weight

Method: OECD Test Guideline 422

Result: Animal testing did not show any effects on fertility.

GLP: yes

Effects on foetal Test Type: reproductive and developmental toxicity study

Species: Rat, male and female development

Application Route: Oral

Dose: 5, 15 and 50 mg/kg bw/d

General Toxicity Maternal: NOAEL: 15 mg/kg body weight Developmental Toxicity: NOAEL: 15 mg/kg body weight

Method: OECD Test Guideline 422

Result: Not classified

GLP: yes

Remarks: Information given is based on data obtained from

similar substances.

Reproductive toxicity -No evidence of adverse effects on sexual function and fertility,

Assessment or on development, based on animal experiments.

# Amines, polyethylenepoly-, triethylenetetramine fraction:

Effects on foetal Test Type: Pre-natal

development Species: Rat

Application Route: Oral

Dose: 75/325/750 mg/kg bw/day Duration of Single Treatment: 10 d

General Toxicity Maternal: NOAEL: >= 750 mg/kg body weight Developmental Toxicity: NOAEL: >= 750 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# HARDENER HV 998-1

Version Revision Date: SDS Number: Date of last issue: 16.07.2022 40000000524 1.5 04.11.2023 Date of first issue: 19.05.2016

Print Date 22.04.2024

Test Type: Pre-natal Species: Rabbit

Application Route: Dermal Dose: 5/50/125 mg/kg bw/day Duration of Single Treatment: 13 d

General Toxicity Maternal: NOAEL: 50 mg/kg body weight Developmental Toxicity: NOAEL: >= 125 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

#### STOT - single exposure

Not classified due to lack of data.

#### STOT - repeated exposure

Not classified due to lack of data.

# Repeated dose toxicity

#### **Components:**

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Species Rat, male and female

NOAEL 1000 mg/kg Application Route Ingestion Exposure time 6 Weeks

Number of exposures 7 d

Method Subacute toxicity

# N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

**Species** Rat, male and female

500 mg/m3

Application Route Inhalation Test atmosphere vapour Exposure time 21 d 6 h Number of exposures 5 days/week 550 mg/m3 Dose

Method Subchronic toxicity

Based on data from similar materials Remarks

Species Mouse, male NOAEL  $>= 56.3 \, \text{mg/kg/d}$ Skin contact Application Route

Number of exposures 3 d

Method Chronic toxicity

Remarks Based on data from similar materials

Species Rat, male and female

NOAEL 41 mg/kg **NOAEL** 1,000 mg/l, ppm Application Route : oral (feed) Exposure time 20 months Number of exposures 3 times/week

Dose 1000/7500/15000 ppm

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAI Enriching lives through innovation

## HARDENER HV 998-1

Version Revision Date: SDS Number: Date of last issue: 16.07.2022 40000000524 1.5 04.11.2023 Date of first issue: 19.05.2016

Print Date 22.04.2024

: OECD Test Guideline 408 Method

Amines, polyethylenepoly-, triethylenetetramine fraction:

Species Rat, male and female

NOAEL 350 mg/kg **Application Route** Oral Exposure time 28 d Number of exposures 7 d

Dose 100/350/1000 mg/kg bw/day Method **OECD Test Guideline 407** 

**Target Organs** Lungs

Remarks Information given is based on data obtained from similar

substances.

Species Dog, male and female

NOAEL 125 mg/kg **Application Route** Oral **Target Organs** Lungs

Remarks Information given is based on data obtained from similar

substances.

**Species** Dog, male and female

50 mg/kg NOAEL **Application Route** Oral

Method Subchronic toxicity

Remarks Information given is based on data obtained from similar

substances.

Rat, male and female Species

NOAEL 50 mg/kg Oral **Application Route** 26 weeks Exposure time

50/175/600 mg/kg bw/day Dose **OECD Test Guideline 408** Method

Target Organs Lungs

Remarks Information given is based on data obtained from similar

substances.

Mouse, male and female **Species** NOAEL 92 mg/kg, 600 ppm

Application Route Oral

Exposure time : 120/600/3000 ppm

Method **OECD Test Guideline 408** 

Information given is based on data obtained from similar Remarks

substances.

barium sulfate:

Species Rat

LOEC >= 104 mg/kg, 40 mg/m3

**Application Route** Ingestion Test atmosphere dust/mist Exposure time 5 h Number of exposures 5 d

Method Subchronic toxicity

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## HARDENER HV 998-1

Version Revision Date: SDS Number: Date of last issue: 16.07.2022 1.5 04.11.2023 40000000524 Date of first issue: 19.05.2016

Print Date 22.04.2024

#### **Aspiration toxicity**

Not classified due to lack of data.

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

No data available

#### **Experience with human exposure**

No data available

#### Toxicology, Metabolism, Distribution

No data available

## **Neurological effects**

No data available

#### **Further information**

No data available

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### **Components:**

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18

(unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 7.07 mg/l

Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 5.18 mg/l

Exposure time: 48 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Selenastrum capricornutum (green algae)): 2.43 mg/l

Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (activated sludge): 421 mg/l

Exposure time: 3 h
Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 209

# N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l

End point: mortality

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## HARDENER HV 998-1

Version Revision Date: SDS Number: Date of last issue: 16.07.2022 1.5 04.11.2023 40000000524 Date of first issue: 19.05.2016

Print Date 22.04.2024

Exposure time: 96 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 9.2 mg/l

End point: Immobilization
Exposure time: 48 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae/aquatic

plants

ErC50 (Selenastrum capricornutum (green algae)): 21 mg/l

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201

GLP: yes

NOEC (Selenastrum capricornutum (green algae)): 5.7 mg/l

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201

GLP: yes

Toxicity to microorganisms : EC50 (Pseudomonas putida): 181 mg/l

Exposure time: 16 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: DIN 38 412 Part 8

GLP: no

Amines, polyethylenepoly-, triethylenetetramine fraction:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): 570 mg/l

Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water

Method: Directive 67/548/EEC, Annex V, C.1.

LC50 (Leuciscus idus (Golden orfe)): 200 - 500 mg/l

Exposure time: 96 h

LC50 (Pimephales promelas (fathead minnow)): 330 mg/l

End point: mortality Exposure time: 96 h Test Type: static test

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# HARDENER HV 998-1

Version Date of last issue: 16.07.2022 Revision Date: SDS Number: 40000000524 1.5 04.11.2023 Date of first issue: 19.05.2016

Print Date 22.04.2024

Test substance: Fresh water Method: EPA OTS 797.1400

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 31.1 mg/l

End point: Immobilization Exposure time: 48 h Test Type: static test Test substance: Fresh water

Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae/aquatic

plants

ErC50 (Selenastrum capricornutum (green algae)): 20 mg/l

Exposure time: 72 h Test Type: semi-static test Test substance: Fresh water Method: OECD Test Guideline 201

EC10 (Selenastrum capricornutum (green algae)): 1.34 mg/l

Exposure time: 72 h Test Type: semi-static test Test substance: Fresh water Method: OECD Test Guideline 201

Toxicity to microorganisms

NOEC (Bacteria): >= 100 mg/l

Exposure time: 28 d

Method: OECD Test Guideline 216

EC50 (Bacteria): > 100 mg/l

Exposure time: 28 h

Method: OECD Test Guideline 216

EC50 (Bacteria): 15.7 mg/l Exposure time: 2 h Test Type: static test

Test substance: Fresh water

NOEC (Bacteria): 1.3 mg/l Exposure time: 2 h Test Type: static test Test substance: Fresh water

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

EC10: 1.9 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test Test substance: Fresh water Method: OECD Test Guideline 202

Toxicity to soil dwelling

organisms

NOEC: ca. 62.5 mg/kg Exposure time: 56 d

Species: Eisenia fetida (earthworms) Method: OECD Test Guideline 222

EC50: > 1,000 mg/kgExposure time: 56 d

Species: Eisenia fetida (earthworms)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## HARDENER HV 998-1

Version Revision Date: SDS Number: Date of last issue: 16.07.2022 1.5 04.11.2023 40000000524 Date of first issue: 19.05.2016

Print Date 22.04.2024

Method: OECD Test Guideline 222

**Ecotoxicology Assessment** 

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

barium sulfate:

Toxicity to fish : LC50 : 174 mg/l

Exposure time: 96 h
Test Type: static test
Test substance: Fresh water

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): 14.5 mg/l

Exposure time: 48 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 : > 100 mg/l

Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 201

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC: 5.8 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

#### 12.2 Persistence and degradability

# Components:

## N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Biodegradability : Test Type: aerobic

Result: Readily biodegradable.

Biodegradation: 100 %

Related to: Dissolved organic carbon (DOC)

Exposure time: 28 d

Method: OECD Test Guideline 301A

Test substance: Fresh water

GLP: yes

# Amines, polyethylenepoly-, triethylenetetramine fraction:

Biodegradability : Inoculum: activated sludge

Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 162 d

Method: OECD Test Guideline 301D

Test substance: Fresh water

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## HARDENER HV 998-1

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 16.07.2022

 1.5
 04.11.2023
 400000000524
 Date of first issue: 19.05.2016

Print Date 22.04.2024

Test Type: aerobic

Inoculum: activated sludge

Result: Not inherently biodegradable.

Biodegradation: 20 %

Related to: Dissolved organic carbon (DOC)

Exposure time: 84 d

Method: OECD Test Guideline 302A

Test substance: Fresh water

#### 12.3 Bioaccumulative potential

#### **Components:**

### N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Partition coefficient: n- : log Pow: -0.56 (25 °C)

octanol/water pH: 11.6

Method: OECD Test Guideline 107

# Amines, polyethylenepoly-, triethylenetetramine fraction:

Partition coefficient: n- : log Pow: -2.08 - 2.90 (20 °C)

octanol/water Method: QSAR

#### 12.4 Mobility in soil

# **Components:**

#### Amines, polyethylenepoly-, triethylenetetramine fraction:

Distribution among : Koc: 3162.28, log Koc: 3.5

environmental compartments Method: OECD Test Guideline 106

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

# 12.6 Endocrine disrupting properties

No data available

#### 12.7 Other adverse effects

#### **Product:**

information

Additional ecological

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## HARDENER HV 998-1

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 16.07.2022

 1.5
 04.11.2023
 400000000524
 Date of first issue: 19.05.2016

Print Date 22.04.2024

Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

# **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADR : UN 3082
RID : UN 3082
IMDG : UN 3082
IATA : UN 3082

# 14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(POLYAMIDE RESIN)

RID : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(POLYAMIDE RESIN)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(POLYAMIDE RESIN)

IATA : Environmentally hazardous substance, liquid, n.o.s.

(POLYAMIDE ŘESIN)

# 14.3 Transport hazard class(es)

Class Subsidiary risks

 ADR
 : 9

 RID
 : 9

 IMDG
 : 9

 IATA
 : 9

# 14.4 Packing group

**ADR** 

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

RID

Packing group : III Classification Code : M6

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# **HARDENER HV 998-1**

Version Revision Date: SDS Number: Date of last issue: 16.07.2022 1.5 04.11.2023 40000000524 Date of first issue: 19.05.2016

Print Date 22.04.2024

Hazard Identification Number : 90 Labels : 9

**IMDG** 

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo : 964

aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

IATA (Passenger)

Packing instruction : 964

(passenger aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

14.5 Environmental hazards

**ADR** 

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

**IMDG** 

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the

following entries should be

considered: Number on list 3

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## HARDENER HV 998-1

Version Revision Date: SDS Number: Date of last issue: 16.07.2022 1.5 04.11.2023 40000000524 Date of first issue: 19.05.2016

Print Date 22.04.2024

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

: Ovaj proizvod ne sadrži supstance

koje izazivaju veliku zabrinutost.

UK REACH List of substances subject to authorisation

(Annex XIV)

: Not applicable

# Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

#### The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AIIC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

#### **Inventories**

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

#### 15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H302 : Harmful if swallowed.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Classification procedure:

## HARDENER HV 998-1

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 16.07.2022

 1.5
 04.11.2023
 40000000524
 Date of first issue: 19.05.2016

Print Date 22.04.2024

H312 : Harmful in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction. H318 : Causes serious eye damage.

H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

#### **Further information**

#### Classification of the mixture:

Skin Irrit. 2 H315 Based on product data or assessment

Eye Dam. 1 H318 Based on product data or assessment

Skin Sens. 1 H317 Calculation method Aquatic Chronic 2 H411 Calculation method

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# HARDENER HV 998-1

Version Revision Date: SDS Number: Date of last issue: 16.07.2022 1.5 04.11.2023 40000000524 Date of first issue: 19.05.2016

Print Date 22.04.2024

PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.