


## RMP24-micro: The world's smallest wireless probe for machine tools

Renishaw's miniature radio probe, measuring just 24 mm in diameter and 31 mm in length, provides fast, accurate and reliable part set-up and verification in a package that fits in the palm of your hand.

### Features and benefits

- Miniature design - Ideally suited to compact machines manufacturing high-value, high-precision parts found in medical, watchmaking and micro-mechanics industries.
- Highly repeatable - High-precision components with tight tolerances can be measured with exceptional repeatability.
- Ultra-low trigger force - Helps eliminate surface and form damage when inspecting soft metal components.



## Next generation radio transmission

RMP24-micro is our latest QE series probing system and communicates with the machine controller via the ultra-compact RMI-QE radio interface. It uses an updated version of our industry-proven frequency hopping spread spectrum (FHSS) transmission technology and operates within the globally recognised 2.4 GHz frequency band. This agile protocol provides robust and reliable communication in busy radio environments and is compliant with radio regulations in all major markets.

### What is frequency hopping spread spectrum (FHSS) radio transmission technology?

FHSS technology enables both the probe and interface to jump from channel-to-channel whilst maintaining communication. This allows our systems to work and co-exist alongside other probes as well as other radio sources such as Wi-Fi, Bluetooth® and microwave ovens as and when they enter the same environment.



Technical highlights	
<b>Unidirectional repeatability</b> Maximum 2σ value in any direction	0.35 μm (14 μin) 2σ *
<b>Transmission type</b>	Frequency hopping spread spectrum (FHSS) radio
<b>Receiver/interface</b>	RMI-QE combined antenna, interface and receiver unit
<b>Stylus trigger force</b> XY low force XY high force Z	0.08 N, 8.2 gf (0.29 ozf) 0.14 N, 16.3 gf (0.58 ozf) 0.75 N, 76.5 gf (2.70 ozf)
<b>Recommended styli</b>	Steel, lengths 10 mm (0.39 in) to 30 mm (1.18 in)

\* Performance specification is tested at a standard test velocity of 480 mm/min (18.89 in/min) with a 10 mm stylus. Significantly higher velocity is possible depending on application requirements.



Dimensions given in mm (in)

[www.renishaw.com/rmp24-micro](http://www.renishaw.com/rmp24-micro)

#renishaw

+44 (0)1453 524524

uk@renishaw.com

© 2023 Renishaw plc. All rights reserved. RENISHAW® and the probe symbol are registered trade marks of Renishaw plc. Renishaw product names, designations and the mark 'apply innovation' are trade marks of Renishaw plc or its subsidiaries. Other brand, product or company names are trade marks of their respective owners. Renishaw plc. Registered in England and Wales. Company no: 1106260. Registered office: New Mills, Wotton-under-Edge, Glos, GL12 8JR, UK.

WHILE CONSIDERABLE EFFORT WAS MADE TO VERIFY THE ACCURACY OF THIS DOCUMENT AT PUBLICATION, ALL WARRANTIES, CONDITIONS, REPRESENTATIONS AND LIABILITY, HOWSOEVER ARISING, ARE EXCLUDED TO THE EXTENT PERMITTED BY LAW.

Part no.: H-6906-8300-01-A