

# ALPHA

## SAFETY DATA SHEET THIXOFIX (Improved)

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME THIXOFIX (Improved)

SUPPLIER Alpha Adhesives & Sealants Ltd  
Llewellyn Close, Sandy Lane Ind.Est.  
Stourport-on-Severn  
Worcestershire DY13 9RH  
01299 828626  
01299 828666  
sales@alpha-adhesives.co.uk

EMERGENCY TELEPHONE 44 (0) 1299 828626 (Available 08.30 to 17.00)

Supplied by:  
RS Components Ltd,  
Hitchington Road, Corby, Northants, NN17 9RS  
Tel: +44 (0) 1536 402888 (8am to 8pm)  
Email: technical.help@rs-components.com

### 2 HAZARDS IDENTIFICATION

Highly flammable. Vapours may cause drowsiness and dizziness. Irritating to eyes and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION (1999/45) Xi;R36/38, F;R11, N;R51/53, R67.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content %	Classification (67/548/EEC)
CYCLOHEXANE	203-806-2	110-82-7	10-30%	F;R11 Xn;R65 Xi;R38 R67 N;R50/53
BUTANONE	201-159-0	78-93-3	10-30%	F;R11 Xi;R36 R66 R67
Naphtha(petroleum),Hydrotreated Light	265-151-9	64742-49-0	10-30%	Xn;R65, Xi;R38, F;R11, N;R51/53, R67.
ACETONE	200-662-2	67-64-1	10-30%	F;R11 Xi;R36 R66 R67
ETHYL ACETATE	205-500-4	141-78-6	10-30%	F;R11 Xi;R36 R66 R67
TOLUENE	203-625-9	108-88-3		F;R11 Repr. Cat. 3;R63 Xn;R48/20,R65 Xi;R38 R67

The Full Text for all R-Phrases is Displayed in Section 16

### COMPOSITION COMMENTS

The data shown are in accordance with the latest EC Directives. Toluene content = 0.0003%

### 4 FIRST-AID MEASURES

#### GENERAL INFORMATION

NOTE! Keep affected person away from heat, sparks and flames!

#### NOTES TO THE PHYSICIAN

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

#### INHALATION

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

#### INGESTION

DO NOT INDUCE VOMITING! Remove victim immediately from source of exposure. Provide rest, warmth and fresh air. Get medical attention.

THIXOFIX (Improved)

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Extinguish with foam, carbon dioxide or dry powder.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

UNUSUAL FIRE & EXPLOSION HAZARDS

HIGHLY FLAMMABLE! Severe explosion hazard when vapours are exposed to flames.

SPECIFIC HAZARDS

Toxic gases/vapours/fumes of: Carbon dioxide (CO2). Carbon monoxide (CO). Hydrogen chloride (HCl).

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Clean-up personnel should use respiratory and/or liquid contact protection. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

STORAGE CLASS

Flammable liquid storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
ACETONE	WEL	750	1810	1500	3620	
BUTANONE	WEL	200	600	300	899	
CYCLOHEXANE	WEL	100 ppm	350 mg/m3	300 ppm	1050 mg/m3	
ETHYL ACETATE	WEL	400	1460 mg/m3			
Naphtha(petroleum),Hydrotreated Light	WEL		1200 mg/m3			
TOLUENE	WEL	50	191	150	574	

THIXOFIX (Improved)

WEL = Workplace Exposure Limit.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation. Maintain efficient ventilation/extraction using flameproof equipment where necessary.

RESPIRATORY EQUIPMENT

Respiratory protection must be used if air contamination exceeds acceptable level.

HAND PROTECTION

Use protective gloves.

EYE PROTECTION

Use approved safety goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

SKIN PROTECTION

Wear apron or protective clothing in case of splashes.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Coloured gel.
COLOUR	Amber.
ODOUR	Organic solvents.
SOLUBILITY	Slightly soluble in water.
BOILING POINT (°C)	110
RELATIVE DENSITY	0.85 - 0.86 @ 20 °c
VISCOSITY	GEL @ 23 °c
FLASH POINT (°C)	-5 CC (Closed cup).
FLAMMABILITY LIMIT - LOWER(%)	1
FLAMMABILITY LIMIT - UPPER(%)	13

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO), Carbon dioxide (CO2), Hydrogen chloride (HCl).

11 TOXICOLOGICAL INFORMATION

## THIXOFIX (Improved)

## INHALATION

When working extensively on big surfaces in small and badly ventilated rooms, vapours may develop in concentrations which may cause headache and irritation of the eyes and the respiratory system. Vapours may cause drowsiness and dizziness.

## INGESTION

May cause stomach pain or vomiting.

## SKIN CONTACT

Irritating to skin.

## EYE CONTACT

Irritating to eyes.

## ROUTE OF ENTRY

Inhalation. Skin absorption.

## MEDICAL SYMPTOMS

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

## SPECIFIC EFFECTS

Contains a substance/a group of substances which may cause harm to the unborn child.

---

**12 ECOLOGICAL INFORMATION**


---

## ECOTOXICITY

Dangerous for the environment if discharged into watercourses. The product contains substances which are toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

## MOBILITY

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

## BIOACCUMULATION

No data available on bioaccumulation.

## DEGRADABILITY

The product is expected to be biodegradable.

## WATER HAZARD CLASSIFICATION

Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

---

**13 DISPOSAL CONSIDERATIONS**


---

## DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

---

**14 TRANSPORT INFORMATION**


---




PROPER SHIPPING NAME	ADHESIVES (CYCLOHEXANE)
UN NO. ROAD	1133
ADR CLASS NO.	3
ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	II
TUNNEL RESTRICTION CODE	(D/E)
HAZARD No. (ADR)	33
ADR LABEL NO.	3
HAZCHEM CODE	•3YE

THIXOFIX (Improved)

UN NO. SEA	1133
IMDG CLASS	3
IMDG PACK GR.	II
EMS	F-E, S-D
UN NO. AIR	1133
AIR CLASS	3
AIR PACK GR.	II

15 REGULATORY INFORMATION

LABELLING



Irritant



Highly flammable



Dangerous for the environment

RISK PHRASES

R11	Highly flammable
R36/38	Irritating to eyes and skin.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.

SAFETY PHRASES

S16	Keep away from sources of ignition - No smoking.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S29	Do not empty into drains.
S37	Wear suitable gloves.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well-ventilated areas.
S64	If swallowed, rinse mouth with water (only if the person is conscious).

UK REGULATORY REFERENCES

Petroleum (Consolidation) Act, as amended 1984 SI 1244.

ENVIRONMENTAL LISTING

Control of Pollution Act 1974.

EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EC.

STATUTORY INSTRUMENTS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

NATIONAL REGULATIONS

Control of Substances Hazardous to Health Regulations 2002 (as amended)

16 OTHER INFORMATION

INFORMATION SOURCES

Dangerous Properties of Industrial Materials Report, N.Sax et.al.

THIXOFIX (Improved)

REVISION COMMENTS

NOTE: Lines within the margin indicate significant changes from the previous revision.

REVISION DATE FEBRUARY 2011

REV. NO./REPL. SDS GENERATED 8

RISK PHRASES IN FULL

- R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- R65 Harmful: may cause lung damage if swallowed.
- R11 Highly flammable
- R36/38 Irritating to eyes and skin.
- R36 Irritating to eyes.
- R38 Irritating to skin.
- R63 Possible risk of harm to the unborn child.
- R66 Repeated exposure may cause skin dryness or cracking.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R67 Vapours may cause drowsiness and dizziness.
- R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.