

SAFETY DATA SHEET

Aluminium AlSi10Mg

SECTION 1: Identification

1.1. Product identifier

Trade name

Aluminium AlSi10Mg

Other names / Synonyms

Document No.: H-5800-3482-02-A_EN

Product no.

A-5771-0403

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Metal powder for additive layer manufacture

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Renishaw plc

New Mills

Wotton-under-Edge,

GL12 8JR, Gloucestershire,

United Kingdom

+44 (0) 1453 524524

www.renishaw.com

E-mail

msds@renishaw.com

SDS date

2/23/2023

SDS Version

1.0

1.4. Emergency telephone number

Contact the poison control at 1-800-222-1222 (24/7) or use the webPOISONCONTROL® (triage.webpoisoncontrol.org) to get specific guidance for your case

See also section 4 "First aid measures".

Emergency contact from supplier: +44 (0) 1453 524524 (UK office hours 08:00 to 17:00 UTC Monday to Thursday, 08:00 to 16:00 Friday)

SECTION 2: Hazard(s) identification

OSHA/HCS status

This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Classification of the substance or mixture

Not classified according to HCS (29 CFR 1910.1200)

2.2. Label elements

Hazard pictogram(s)

Not applicable.

Signal word

Not applicable.

Hazard statement(s)

Not applicable.

Safety statement(s)

General

-

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012)

Prevention

-

Response

-

Storage

-

Disposal

-

Additional labelling

Not applicable.

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

May form explosible dust-air mixture if dispersed.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Aluminium powder (stabilised)	CAS No.: 7429-90-5	87.3%	Flam. Sol. 1, H228 Water-react. 2, H261	
Silicon	CAS No.: 7440-21-3	11%		

Where the concentration of an ingredient is expressed as a range the exact concentration has been withheld as a trade secret.

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

None known.

SECTION 4: First-aid measures

4.1. Description of first aid measures

General information

If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 911 and give immediate treatment (first aid).

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Upon irritation: rinse with water. In the event of continued irritation, seek medical assistance.

Eye contact

Upon irritation of the eye: Remove contact lenses. Flush eyes with plenty of water or salt water (20-30 °C) and continue until irritation stops.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012)

None known.

4.3. Indication of any immediate medical attention and special treatment needed

None known.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media: Dry powder (Class D), sodium chloride (granulate) or dry sand.

Unsuitable extinguishing media: DO NOT USE WATER!

Suitable extinguishing media: Use class D extinguishing agents on dust, fines or molten metal.

Unsuitable extinguishing media: Water, foam, halogenated extinguishing agents.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the Poison Help Line on 1-800-222-1222 (24/7) in order to obtain further advice.

Fire fighters should wear appropriate personal protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.

Evacuate surrounding areas.

Eliminate all ignition sources.

Ventilate the area.

Wear appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. Methods and material for containment and cleaning up

Collect spills carefully. Moist the material with water in order to prevent the formation and propagation of dust.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

Use spark-proof tools and explosion-proof equipment.

Avoid dust generation.

Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Avoid the suspension of dust in the air.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use non-sparking tools.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

Store in tightly closed original container in a dry, cool and well-ventilated place.

Store in accordance with local regulations.

Incompatible materials

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012)

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Aluminium powder (stabilised)

Long term exposure limit (OSHA Table Z-1) (mg/m³): 15 Total dust / 5 Respirable fraction

Long term exposure limit (ACGIH TLV) (mg/m³): 1 Respirable fraction

Long term exposure limit (NIOSH REL) (mg/m³): 10 (Total dust), 5 (Respirable fraction)

Silicon

Long term exposure limit (OSHA Table Z-1) (mg/m³): 15 (total dust) / 5 (Respirable fraction)

Long term exposure limit (NIOSH REL) (mg/m³): 10 (Total dust), 5 (Respirable fraction)

Part 1910 - Occupational Safety and Health Standards (29 CFR 1910.1000 TABLE Z-1 - Limits for Air Contaminants)

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

Where necessary use lighting and electrical equipment designed for use in atmospheres where flammable vapours or dusts are present, and which can direct static electricity by grounding equipment.

General recommendations

When transferring the materials, dust clouds should be kept at an absolute minimum. Handling should be slow and deliberate. The materials should be transferred from one container to another using a non-sparking, conductive metal scoop.

When mixing the material with other dry ingredients, frictional heat should be avoided. The best type of mixer for a dry mixing operation is one that contains no moving parts, but rather affects a tumbling action, such as a conical blender. Introduction of an inert atmosphere in the blender is highly recommended since dust clouds are generated. All equipment must be well grounded.

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above).

Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and showers are clearly marked.

Hygiene measures

Wash hands after use.

Measures to avoid environmental exposure

No specific requirements.


Individual protection measures, such as personal protective equipment

Generally

Use only protective equipment with a recognized certification mark, e.g. the UL mark.


Respiratory Equipment

Type	Class	Colour	Standards
SL	P3	White	EN149





Skin protection

Recommended	Type/Category	Standards
Protective footwear	Protective footwear	
Dedicated work clothing should be worn. Wear a protective suit in the event of prolonged	-	-



Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012)

Recommended	Type/Category	Standards			
periods of work with the product.					
Hand protection					
Material	Glove thickness (mm)	Breakthrough time (min.)	Standards		
Butyl	0,3	> 480	EN374-2, EN374-3, EN388		
Eye protection					
Type	Standards				
Safety glasses with side shields.	EN166				

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Powder

Colour

Gray

Odour

None

Odour threshold (ppm)

Testing not relevant or not possible due to the nature of the product.

pH

Not applicable - product is a solid

Density (g/cm³)

2.67

Kinematic viscosity

Not applicable - product is a solid

Phase changes

Melting point (°F)

No information available as testing has not been completed.

Boiling point (°F)

No information available as testing has not been completed.

Vapour pressure

Testing not relevant or not possible due to the nature of the product.

Vapour density

Does not apply to solids.

Decomposition temperature (°F)

No information available as testing has not been completed.

Evaporation rate (n-butylacetate = 100)

Not applicable - product is a solid

Data on fire and explosion hazards

Flash point (°F)

Does not apply to solids.

Flammability (°F)

Testing not relevant or not possible due to nature of the product.

Auto-ignition temperature (°F)

Testing not relevant or not possible due to nature of the product.

Explosion limits (% v/v)

Does not apply to solids.

Solubility

Solubility in water

Insoluble

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012)

n-octanol/water coefficient

No information available as testing has not been completed.

9.2. Other information

Solubility in fat (g/L)

No information available as testing has not been completed.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid the suspension of dust in the air.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Product/substance	Silicon
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	> 5000 mg/kg

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Long term effects

None known.

Other information

None known.

Exposure to metal dusts and oxides may cause metal fume fever. Metal fume fever is a temporary flu-like condition characterized by chills, fever, muscle aches and pains, nausea, and vomiting. Typically, the symptoms appear within a few hours after exposure and subside within 2-3 days with no permanent effects.

SECTION 12: Ecological information

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012)

12.1. Toxicity

No data available.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

Product/substance Silicon

Test method:

Potential bioaccumulation: No data available.

LogPow: 54 - 77 (25°C, pH 7 - 8)

BCF: No data available.

Other information:

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Other adverse effects

None known.

SECTION 13: Disposal considerations

RCRA Hazardous waste ("P" and "U" list) (40 CFR 261)

None of the components are listed

Specific labelling

Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
DOT	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

* Packing group

** Environmental hazards

Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. U.S. Federal regulations

TSCA

Aluminium powder (stabilised) is listed in the non-confidential portion

Silicon is listed in the non-confidential portion

Clean Air Act

None of the components are listed

EPCRA Section 302

None of the components are listed

EPCRA Section 304

None of the components are listed

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012)

EPCRA section 313

Aluminium powder (stabilised) is listed

CERCLA

None of the components are listed

State regulations

California / Prop. 65

None of the components are listed

Massachusetts / Right To Know Act

Aluminium powder (stabilised) is listed
Silicon is listed

New Jersey / Right To Know Act

Aluminium powder (stabilised) / Substance number: 0054
Aluminium powder (stabilised) is on the Special Health Hazard Substance List

—
Silicon / Substance number: 3125

Silicon is on the Special Health Hazard Substance List

New York / Right To Know Act

Aluminium powder (stabilised) is listed
Aluminium powder (stabilised) is regulated with a Treshold Reporting Quantity (TRQ) of: 1 pounds

Pennsylvania / Right To Know Act

Aluminium powder (stabilised) is listed
Aluminium powder (stabilised) is hazardous to the environment (E)

—
Silicon is listed

15.4. Restrictions for application

Restricted to professional users.

15.5. Demands for specific education

No specific requirements.

15.6. Additional information

Not applicable.

15.7. Chemical safety assessment

No

15.8. Sources

OSHA Hazard Communication Standard (29 CFR 1910.1200)

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H228, Flammable solid.

H261, In contact with water releases flammable gases.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CERCLA = Comprehensive Environmental Response Compensation and Liability Act

EINECS = European Inventory of Existing Commercial chemical Substances

EPCRA = Emergency Planning and Community Right-To-Know Act

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

HCIS = Hazardous Chemical Information System

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012)

1978. ("Marpol" = marine pollution)
NFPA = National Fire Protection Association
NIOSH = National Institute for Occupational Safety and Health
OECD = Organisation for Economic Co-operation and Development
OSHA = Occupational Safety and Health Administration
PBT = Persistent, Bioaccumulative and Toxic
RCRA = Resource Conservation and Recovery Act
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SARA = Superfund Amendments and Reauthorization Act
SCL = A specific concentration limit.
STEL = Short-term exposure limits
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TSCA = The Toxic Substances Control Act
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

Not applicable.

The safety data sheet is validated by

EcoOnline

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: US-en